

Chart for configuration of individual sealings type HRD for cables

Core drill/wall sleeve ID (mm)	Number of cables	Max. cable OD (mm)
50	1	0 – 26
	3	0 – 14
	6	0 – 5
60	1	0 – 36
	3	0 – 19
	6	0 – 9
70	1	0 – 46
	3	0 – 23
	6	0 – 13
80	1	0 – 56
	3	0 – 28
	6	0 – 18
100	1	0 – 76
	3	0 – 37
	6	0 – 25
125	1	0 – 101
	3	0 – 49
	6	0 – 33
150	1	0 – 125
	3	0 – 60
	6	0 – 42
200	1	0 – 171
	3	0 – 84
	6	0 – 58
250	1	0 – 214
	3	0 – 107
	6	0 – 75

The values shown in this chart are configuration examples which shall give you an indication. Diam. and number of cable entries are variable and individual sealings are manufactured according to your requirements. Our sales people are ready to help you with any questions concerning our products and services.

TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDING
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIA
ABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE
BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.F
ABLE.PIPE BUILDINGENTRY ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY
TRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALV
LWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.B
BUILDINGENTRY ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.F
AYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIG
LE ALWAYS.TIGHT CABLE.PIPE.BUILDINGENTRY. ALWAYS ALWAYS ALWAYS TIGHT.CABLE.P
LE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.AL
ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDINGENTRY ALWAYS.RELIABLE ALWAYS
S.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE PIPE BUI
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDINGENTRY ALWAYS.FIA
CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDING
NTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE BUILDINGENTRY ALWAYS.FIABLE

ALWAYS HAUFF