

# Chart for configuration of individual sealings type HRD for pipes

Core drill/wall sleeve ID (mm)	Number of pipes	Max. pipe OD (mm)
50	1	0 – 26
60	1	0 – 36
70	1	0 – 46
80	1	0 – 56
100	1	0 – 76
125	1	0 – 101
150	1	0 – 125
200	1	0 – 171
250	1	0 – 214
300	1	0 – 250
350	1	0 – 300
400	1	0 – 350
450	1	0 – 400
500	1	0 – 450

The values shown in this chart are configuration examples which shall give you an indication. Diam. and number of cable entries are variable and individual sealings are manufactured according to your requirements. Our sales people are ready to help you with any questions concerning our products and services.

TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDING  
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIA  
ABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE  
BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.F  
ABLE.PIPE BUILDINGENTRY ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY  
TRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALV  
LWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.B  
BUILDINGENTRY ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.F  
AYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIG  
LE ALWAYS.TIGHT CABLE.PIPE.BUILDINGENTRY. ALWAYS ALWAYS ALWAYS TIGHT.CABLE.P  
LE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE ALWAYS.TIGHT.CABLE.PIPE.BUILDINGENTRY.AL  
ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDINGENTRY ALWAYS.RELIABLE ALWAYS  
S.TIGHT.CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE ALWAYS TIGHT.CABLE PIPE BUI  
DINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDINGENTRY ALWAYS.FIA  
CABLE.PIPE.BUILDINGENTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE PIPE BUILDING  
NTRY.ALWAYS.RELIABLE.ALWAYS.TIGHT.CABLE.PIPE BUILDINGENTRY ALWAYS.FIABLE

# ALWAYS HAUFF