

# Universal wall sleeve

for any type of wall

## UFR150/300 B

Article no.: 3030466850, GTIN: 4052487243162



- **Printed scale for adjusting to specific wall thickness**

- **Flange connection for the processing of plastic-modified bitumen thick coatings**
- **Tried and tested solution for use in fresh concrete composite systems**

Enables sealing in all types of wall when combined with sealing flange and 3-bridge seals. Can be cut to length on site to specific wall thickness using printed scale.



Picture may differ from selected product

## FACTS

### Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

### Scope of delivery:

- 2 pieces closing covers



## Properties:

- FHRK-certified
- Break-resistant, inherently stable
- Sealed ready for installation

## Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

## Tightness:

- gastight and watertight

## FEATURES

D1 (mm):	150
D2 (mm):	162
D4 (mm):	260
D3 (mm):	282
Lenght (mm):	300

## PICTURES

