

Sealing set

for corrugated cable ducts and media pipes

WRD300 1x175 b60 A2/EPDM55

Article no.: 3030327742, GTIN: 4052487241243



- **optical and tangible installation security due to integrated control opening**
- **Patented ring clip technology keeps the closing pressure constant and uniform and prevents deformations**



Picture may differ from selected product

For sealing corrugated cable ducts and media pipes. The patented ring clips in the corrugated section prevent deformations and damage to the corrugated pipe and at the same time keep the closing pressure of the press seal uniform and constant. The insulation ring included in the scope of supply centres the corrugated pipe on the inside of the building and neatly finishes the wall connection.

FACTS

Scope of delivery:

- 1 piece Standard press seal HSD
- Stainless steel ring clips
- 1 piece Insulation ring, split

Dimensions:

- Sealing width: 40, 60 or 80 mm (depending on corrugated pipe)



Properties:

- FHRK-certified
- Ring clips are produced according to the profile supplied by the manufacturer of the corrugated pipe

Application range:

- Waterproof concrete stress class 1

Material:

- All metal parts: stainless steel V2A (AISI 304L)
- Rubber seal: EPDM
- Insulation ring: Styrodur (XPS)

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	300
Nominal width (mm):	175
Type:	THERMO SINGLE/TWIN DN175

PICTURES

