

Flexible earthing entry

HEA PF M12/3000

Article no.: 1700060060, GTIN: 4052487136822



- **Patented twist resistance provided by special contour of contact washer**

With flexible steel cable for positioning earthing connections which can be adjusted both up and down and from side to side. A cross-clamp (accessories) provides an ideal means of making a reinforcement connection.



Picture may differ from selected product

FACTS

Advantages:

- Flexible cross-clamp connection in concrete is possible
- Shifting of connection positions, set in concrete in several sections
- Water barrier for tightness with concrete
- Watertight M12/M16 connection thread on both sides (blind hole)
- Resistant to corrosion

Scope of delivery:

- 2 pieces Protective covers with 4 nail holes

Dimensions:

- Conductor core: round, Ø 25 mm
- Contact washer: Ø 72 mm
- Steel cable: Ø 10 mm

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Conductor core and contact washers: stainless steel V4A (AISI 316L)
- Steel cable: galvanised
- Water barrier: NBR
- Protective covers: PE

Tests/Standards:

- DIN 18014
- DIN EN 62305-3
- VDE 0185-305-3 (with lightning protection application)

FEATURES

Threaded bolt:	M12
wall thickness (mm):	3000