

# Standard press seal

with graduated super segmented ring technology

## HSD100 SSG 1x25/32/40/50/63 b40 A2/EPDM

Article no.: 3030300058, GTIN: 4052487223713



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**

For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Can be adapted to the most common cable diameters on site.



Picture may differ from selected product

## FACTS

### Advantages:

- Split as standard  $\varnothing$  100 mm
- Can be split on site at and above  $\varnothing$  150 mm for retrofit installation
- All manner of material combinations are available for tailor-made applications
- Available from stock

### Dimensions:

- Sealing width: 40 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Openings:	1
Carrier pipe $\varnothing_a$ (mm):	25/32/40/50/63
Packing unit:	15

## PICTURES

