

Plastic spiral conduit hose for cable entry system

Hateflex14090/6000B

Article no.: 3030366907, GTIN: 4052487233064

- Flexible plastic spiral hose (peak compressive strength 745 N).
 - A pressure-tight cable entry system (for up to 2.5 bar external pressure) can be created using the associated connection components.

Flexible and very rugged plastic spiral hose. A pressure-tight cable entry system can be created with the associated connection components.



Picture may differ from selected product

FACTS

Advantages:

- Empty conduit route without sleeve available up to 25 m
- Empty conduit system that can be built over
- Smooth inner surface for gentle cable pulling

Scope of delivery:

• Coils in lengths of 25 m (special lengths are available in 0.5 m sections)

Dimensions:

- ID: 91 mm ± 1 mm
- OD: 104 mm ± 1 mm

Properties:

- Peak compressive strength: 745 N
- Installation temperature: +5°C to +50°C
- Weatherproof and will not rot
- Resistant to brine and seawater
- Installation temperature from +5° to +50°C
- Weather-proof, UV-resistant and rot-resistant
- Resistant to brine and seawater

Material:

Hard PVC/soft PVC

Tightness:

• gastight and watertight to 2.5 bar

FEATURES

Length (m): 6.0

PICTURES





Tel.: +41 62 206 00-70

Fax: +41 62 206 00-79