

Standard press seal

with infinitely super segmented ring technology

HSD150 SSG 1x70-112 b40 A4/NBR55

Article no.: 3030431511, GTIN: 4052487238694



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**



Picture may differ from selected product

For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Infinitely adjustable to cable diameters on site.

FACTS

Advantages:

- Split as standard for retrofit installation
- All manner of material combinations are available for tailor-made applications
- Available from stock

Dimensions:

- Sealing width up to \varnothing 250 mm: 40 mm
- Sealing width for \varnothing 300 mm: 50 mm

Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

Tightness:

- gastight and watertight
- radon tight

FEATURES

| | |
|--|--------|
| Wall sleeve/core drilled hole ID (mm): | 150 |
| Openings: | 1 |
| Carrier pipe \varnothing_a (mm): | 70-112 |
| Packing unit: | 1 |

PICTURES

