

Standard press seal

for rainwater utilisation systems

HSD100 RW 1x25/32/40+3x6-18 b40 A2/EPDM5

Article no.: 3030300059, GTIN: 4052487112499



- **optical and tangible installation security due to integrated control opening**
- **Integrated segmented ring technology for individual adjustment to cable diameters on site**

For sealing new media pipes/cables to be installed or media pipes/cables that have already been laid in core drills or wall sleeves, specially adapted for rainwater utilisation systems.



Picture may differ from selected product

FACTS

Advantages:

- Split as standard for retrofit installation
- Available from stock

Scope of delivery:

- 1 packing unit: 5 items

Dimensions:

- Sealing width: 40 mm
- For core drills/wall sleeves Ø: 100 mm
- For 4 cables/pipes of which 3 x Ø 6-18 mm and 1 x Ø 25, 32 or 40 mm



Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L)
- Rubber: EPDM

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Number of cables/medium overall:	4
Number of cables/medium:	1
	3
Carrier pipe OD (mm):	25/32/40
	6-18
Packing unit:	1

PICTURES

