

# System cover

with sleeve method for corrugated cable ducts

## HSI150 MA110 WR

Article no.: 2126010113, GTIN: 4052487124980

• Mechanical fixing (bayonet) and seal (clamping nut) act independently

- Bayonet system with return lock and locking screw connection (for protection against automatic opening)
- Patented ring clip method

For use in wall insert and plastic flange HSI150. For connecting corrugated cable ducts. The seal is created with the sleeve method, with a rubber sleeve being clamped onto both the system cover and the duct with clamping straps.



Picture may differ from selected product

## FACTS

#### **Advantages:**

• Mechanically stable, elastic connection with system sleeve

#### Scope of delivery:

- incl. sleeve with clamping straps
- incl. ring clips

#### **Properties:**

- FHRK-certified
- For the duct connection Da=160 mm, we recommend using the spacer HSI AH40 to extend the centre distance when installing multiple HSI150 wall inserts



#### Material:

- System cover: polycarbonate
- Clamping nut: PC/PBT blend
- Sleeve: EPDM
- Clamping straps: W4
- Ring clips: stainless steel

#### **Tightness:**

• gastight and watertight to 0.5 bar

### **FEATURES**

Pipe OD:110Manufacture:Fränkische RohrwerkeType:KABUFLEX

### PICTURES



## ACCESSORIES REQUIRED



Flexible socket wrench