

Membrane injection system

for buildings with a basement

MIS90D 1x24-40+3x7-13+2x5-8+2x7 L SET

Article no.: 3030300149, GTIN: 4052487215077

- Universal building entry with membrane injection system for drill holes in the most common types of wall
 - Controlled ejection of resin through slit membrane hose
 - Simultaneous sealing of power and communication services

For reliable sealing of all electricity and telecommunications lines without additional shrinking using a sealing sleeve.



Picture may differ from selected product

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Flexibility provided by sealing sleeve with segmented ring technology

Scope of delivery:

- 1 packing unit:
- 6 pieces MIS 90 including pre-mounted sleeve cap
- 6 pieces wall collars

Dimensions:

• For core drills ID: 92 - 102 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, counter-bearing, sleeve cap, wall rosette, membrane hose: EPDM
- Resin filler hose: PE
- Pipe: PVC-U
- Sealing tape: butyl
- Stainless steel clamping straps: V2A (AISI 304L)

Tightness:

• gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium overall:	8
Number of cables/medium:	1
	3
	2
	2
Suitable for medium pipe OD (mm):	24-40
	7-13
	5-8
	7
Overall lenght (mm):	1300
wall thickness (mm):	900 - 1.200
Packing unit:	1

PICTURES







ACCESSORIES REQUIRED



Tel.: +41 62 206 00-70

Fax: +41 62 206 00-79