

Standard press seal

with segmented ring technology

HRD100 SG 1x24-52 b40 A2/NBR

Article no.: 3030329095, GTIN: 4052487245210



- **Segmented ring technology for adjustment to three or five different pipe diameters on site**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

FACTS

Advantages:

- Empty openings are blind sealed ex works
- Split seal for retrofit installation
- Available from stock

Scope of delivery:

- Blind plugs
- 1 piece Lubricating stick

Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm



Properties:

- FHRK-certified

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L), (V4A (AISI 316L) on request)
- Rubber: EPDM

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Number of cables/medium overall:	1
Openings:	1
Carrier pipe \varnothing_a (mm):	24-52

PICTURES

