

# Standard press seal

sealing width 40 mm

## HSD100 1x48 b40 A2/KTW55

Article no.: 1650010050, GTIN: 4052487121484



- **optical and tangible installation security due to integrated control opening**

For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Available for delivery for all standard pipe sizes.



Picture may differ from selected product

## FACTS

### Advantages:

- Can be split on site up to  $\varnothing$  200 mm for retrofit installation
- Split as standard at and above  $\varnothing$  250 mm
- All manner of material combinations are available for tailor-made applications
- Available from stock

### Dimensions:

- Sealing width: 40 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM, NBR or with KTW approval

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

|                                   |       |
|-----------------------------------|-------|
| Wall sleeve ID (mm):              | 100   |
| Suitable for medium pipe OD (mm): | 48-51 |

## PICTURES

