

Membrane injection system

for buildings without a basement

MIS40S 2x5-7 Set10

Article no.: 3030380167, GTIN: 4052487229883

- Universal building entry with membrane injection system for drill holes in the most common types of wall
 - Controlled ejection of resin through slit membrane hose
 - Sealing lips ensure gentle seal for media lines

Suitable for sloping entry through the wall or floor slab.



Picture may differ from selected product

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533

Scope of delivery:

- 1 packing unit:
- 10 pieces MIS 40S
- 10 pieces wall terminator element
- 10 pieces 2-component resin RESINATOR, 150 ml
- 1 piece quick tensioning device MIS40 SVS

Dimensions:

- For core drills ID: 40 50 mm
- Overall length: 1300 mm

Application range:

- DIN 18533 W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange and counter-bearing
- Resin filler hose: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate
- Fast arrangement fixture: glass fibre reinforced polyamide/ABS

Tightness:

• gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium: 2
Suitable for medium pipe OD

(mm): 5 - 7

Overall lenght (mm): 1300 wall thickness (mm): 200 - 1.200

PICTURES



ACCESSORIES REQUIRED



Quick tensioning device

Tel.: +41 62 206 00-70

Fax: +41 62 206 00-79