

Fixed/loose flange wall sleeve made from stainless steel

for retrofit dowelling for black tank according to DIN 18533

FLFA1x80/80/0 DIN18533 A2

Article no.: 2500400001, GTIN: 4052487062329

For dowelling with wall sleeves, core drills or breakthroughs.



Picture may differ from selected product

FACTS

Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters

Scope of delivery:

- 1 piece Fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- Fastenings for concrete

Dimensions:

- Standard fixed flange $\varnothing a$ equal to the relevant wall sleeve $\varnothing i$ + approx. 330 mm (for one passage)
- Standard upper length: 80 mm

Application range:

- DIN 18533 W2.1-E, DIN 18533 W2.2-E

Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Fastenings: stainless steel V4A (AISI 316L)
- Closing cover: PE


Tightness:

- gastight and watertight

FEATURES

Wall sleeve ID (mm) D1:	80
Fixed flange OD (mm) D2:	405
Loose flange OD (mm) D3:	395
Wall sleeve wall thickness (mm) S:	2

PICTURES



ACCESSORIES REQUIRED



Rubber inlays