

Single wall insert with foldable rubber sleeve

for setting in concrete and connecting smooth cable ducts

HSI150 1x1 KMA163/120

Article no.: 3030319966, GTIN: 4052487224086



- **New foldable rubber sleeve with additional pull out safety through the clamping strap**
- **Readily available for wall thicknesses 120 mm and above**
- **Pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above**
- **Quality mark: sealed ex works. Option to check for accidental or unauthorised opening of the closing cover**



Picture may differ from selected product

For the connection of system seals for cables (inside) on one side and the connection of cable ducts (outside) on the other.

FACTS



Advantages:

- Sturdy Blind cover, formwork aid and a protective cover in one
- Connection possibility for a system seal on one side and with integrated rubber sleeve for connection of smooth cable ducts on the other side
- Defined insertion depth of the cable duct through a stop in the rubber sleeve
- Stronger hold through the increased insertion depth, even in case of a deflection of the cable duct

Scope of delivery:

- 1 piece pressure-tight system cover HSI150 DTS
- 2 pieces HSI150 AH40 spacer
- 1 piece blind cover
- 2 pieces clamping straps

Dimensions:

- Frame dimensions: 220x 220 mm
- Centre distance with spacer: 250 mm

Properties:

- FHRK-certified
- DVGW-certified

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Closing cover: ABS with TPE seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

Tightness:

- gastight and watertight
- radon tight

FEATURES

: 163
wall thickness
(mm): 120

PICTURES

